

RECEIVER

Continuously Variable Sensitivity Control
On / Off with Time-Out

Sharp Audio Tone for Precise Pinpointing

All Weather, Cast Aluminum Housing

Watertight Reinforced Wand

Fast-response Signal Strength Meter

Frequency Selector Switch
(reverse side 800-HL only)

Ergonomic Grip for One-Handed Operation

All Weather, High Impact, UV Protected, ABS Housing

Audio Tone Indicates Battery Strength and Good Connection / Signal

Jack for Direct Connect Cables or optional Signal Clamp

On / Off Switch



TRANSMITTER

Industry's Best High Frequency Induction
Simultaneous Conduction at 9 kHz and 480 kHz



Model 800-HL

- Included: Heavy Duty Conductive Cables
Inductive Sweep Handle
Ground Rod
Light-weight, space-saving Carry Bag
Quick Guide
Instruction Manual

800 Series Comparison Chart		800-H High Freq. Locator	800-HL Dual Freq. Locator
Receiver	Battery:	Two 9 volt	Two 9 volt
	Battery Life (continuous use):	45 hours	45 hours
	Weight:	3.4 lbs (1.5kg)	3.4 lbs (1.5kg)
	Audible Signal Response:	Yes	Yes
	Visual Signal Response:	Yes	Yes
Transmitter	Frequencies:	480 kHz	9 kHz, 480 kHz
	Conductive Mode:	Yes	Yes
	Inductive Mode:	Yes	Yes
	Battery:	8 "C" cells	8 "C" cells
	Battery Life:	40 hours	30 hours
	Batt. Life Indicator:	Yes	Yes
	Good Signal Indicator:	Yes	Yes